

Specifications		
Bridge Voltage	10V DC, 2.5 V ±10% (30mA current maximum, remote sense can be used)	
Signal input range	±3.2 mV/V	
Equivalent input/TEDS	Calibration range	0.3 mV/V-3.2 mV/V
	Calibration precision	Within 0.1% F.S. (when using a 1m standard TEAC Φ8, 4-core shielded cable with 350Ω impedance, 10V BV and 0.5mV/V or greater setting)
Precision	Nonlinearity	Within 0.01% F.S. + 1 digit (when input is 1 mV/V or greater)
	Zero drift	Within 0.5 μV/°C (input conversion value)
	Gain drift	Within ±0.005% F.S./°C
A/D conversion	24-bit, 4000 times per second, 20000 times per second (fast sampling mode)	
Digital filter	Select 3 Hz (-6db/oct), 10, 30, 100, 300, 1000 Hz (-12 db/oct) or none	
D/A output	4000 times per second, isolated output, ±1-±10V voltage output (set in 1V steps) and about 1/59000 resolution (when set to ±10V), or 4-20mA current output and about 1/43000 resolution	
TEDS function		
Display	IEEE1451.4 class 2 mix mode interface	
Indicator value	320 x 240 color liquid crystal	
Indicator value	Display range	-99999 - 99999
	Decimal point	Display position selectable
Displayed items	Times displayed	Select 4, 6, 10 or 20 times/second
	Calibration settings	Zero calibration/span calibration (TEDS calibration, actual load calibration, equivalent input calibration)
Displayed items	Function settings	High limit, low limit, high high limit, low low limit, comparison mode, hysteresis, nearly zero, moving average, low pass filter, motion detect, zero tracking, static strain, digital zero, digital zero offset, zone definition, hold mode, key lock, minimum grid, display times, bridge voltage, digital zero limit, clear digital zero, comp. output pattern, comparison output control, select data output, D/A converter, remote sense
	Hold functions	Sample hold, peak hold, bottom hold, peak to peak hold, peak and bottom hold, average hold, zone definition hold (peak, bottom, peak to peak, peak and bottom, average)
External input and output signals	Input	Hold, judge, clear, digital zero, setting memory selection 1, setting memory selection 2 (isolated from main unit circuits using a photocoupler)
	Output	HH, HI, OK, LO, LL open collector output (isolated from main unit circuits using a photocoupler)
Power supply specifications	CC-Link*	DA, DB (isolated from main unit circuits using a photocoupler), DG, SLD
	RS-485**	A+, B- (isolated from main unit circuits using a photocoupler), TRM, FG
Operating temperature range	0°C - 40°C	
Storage temperature range	-20°C - 60°C	
Operating humidity range	85% RH or less (without condensation)	
Applicable standards	CE marking EN61326 (class A), UL61010-1	
External dimensions (W × H × D)	Approximately 96 mm × 53 mm × 132 mm (without protrusions)	
Weight	About 300 g	

*Only with CC-Link option.
**Only with RS-485 option.
• Weight and dimensions are approximate.

Included accessories

- Panel attachment fixtures (already attached to unit) 2 pcs.
- DIN rail attachment adapter 1 pc.
- Input and output connector plugs
B2L 3.50/08/180F SN BK BX 1 pc.
B2L 3.50/16/180F SN BK BX 1 pc.
- Micro screw driver (flat-blade) 1 pc.
- Operation manual(A5) 1 pc.



Panel attachment fixtures

DIN rail attachment fixtures


Options*

- Several options are available
- CC-Link Interface TD-700T (CCL)
 - RS-485 Interface TD-700T(485)
- * For details, please contact TEAC sales or distributors

Pin Assignment

PIN	ASSIGN	PIN	ASSIGN	PIN	ASSIGN
1	TEDS	9	V-OUT	17	SEL2
2	GND	10	I-OUT	18	COM
3	+EXC	11	COM	19	LL
4	-SIG	12	CLEAR	20	LO
5	-EXC	13	JUDGE	21	HH
6	+SIG	14	HOLD	22	HI
7	SHIELD	15	D/Z	23	OK
8	NC	16	SEL1	24	COM

External Drawing




<https://loadcell.jp/en/>

TEAC AMERICA, INC.



10410 Pioneer Blvd. Suite 1, Santa Fe Springs, California 90670, U.S.A.
TEL: +1-323-726-0303 | FAX: +1-323-727-7632
<http://www.teac.com/>
Email datarecorder@teac.com

Company names and product names in this document are the trademarks or registered trademarks of their respective owners.
Features and specifications are subject to change without notice.
Precaution : To ensure safe handling and operation, read the Instruction Manual before use.




Optionally supports interfaces for easy connection with production lines and other systems: **CC-Link** **RS-485**

High-performance in compact design
Excellent cost performance
High speed processing at 4000 times / sec
(20,000 times / sec at hold)



Actual size



<https://loadcell.jp/en/>

English manual and Chinese manual are available for download from TEAC Load-cell Products Web site



TEAC's TD-700T was developed to measure and display load, pressure, and torque measurements accurately and graphically. The TD-700T brings features to a 1/8 DIN size indicator that are normally found in larger HMI displays.




Feature

High-performance color graphic LCD screen

Vivid display gives immediate process status. Each alarm intuitively and independently advises process condition.

Plug-and-Play (TEDS)

The TD-700T Supports IEEE 1451.4 TEDS. By utilizing TEAC load cells, auto-calibration is performed which eliminates complicated calibration and prevent human error.



TEDS information can be confirmed.

TEAC has various TEDS load cells for Plug-and-Play operation



▼ For more information
<https://loadcell.jp/en/>

Remote Sense Function

Compensates for possible voltage changes due to temperature fluctuations and/or extended cable lengths without the lose of accuracy.




Any changes due to temperature or wire resistance fluctuations

Compensated by the TD-700T.

4000 times / second (★ 20000 times / sec at hold) high-speed processing

Sampling and response times of 4000 per second. You can realize higher measurement accuracy and reliability with faster sampling of 20,000 cycles/s in Fast mode.



Zero Position Bar Graph Settings

Zero position for the bar graph can be set automatically depending upon the application.

Positive & negative value sample hold

TD-700T can sample, hold and average both positive and negative values. It can be used in measurements using dual pole devices such as torque sensors.

Comparison function


It is possible to set up to 4 values (HHI, HI, LO and LLO) to compare with the input signal. The definition of those values is programmable (i.e. 3 upper limits and 1 lower limit). This provides users with a wide variety of alarm applications, and helps avoid confusion and/or problems monitoring your process.

Static strain display

Allows the measure static strain. This function makes it easier to check load-cells for deterioration and plastic deformation.

User friendly warnings

TD-700T detects overloading, wrong connection, invalid parameters and improper adjustments and show warnings on the front LCD.



Analog voltage /current output (isolated)


TD-700T can also be used as a signal conditioner.

4 patterns of memory function


Settings for up to 4 holding modes can be saved. You can switch among those saved.

Examples of information on the display


Visual Alarm Modes




Bar Graph



Actual Process Waveform



Static strain



Numbers only



The fast 4Ks/S sampling rate shows the process levels vividly and in real time. The TD-700T shows what happens before, during and after any event. A variety of display modes is available to meet your purpose.

Example of hold functions


Variety of hold function with block setting

A variety of holding functions can be activated utilizing the front panel controls or external control signals.


★ Fast sampling mode (20000 times/sec) supported

Hold functions	Zone definition
Sample hold	
Peak hold	<input type="radio"/>
Bottom hold	<input type="radio"/>
Peak-to-peak hold	<input type="radio"/>
Peak-and-bottom hold	<input type="radio"/>
Average hold	<input type="radio"/>


Peak hold No zone definition




Peak hold Zone definition used




Bottom hold



Peak to peak hold



Peak and bottom hold



Average hold

